

# Rectifier Diodes

## Avalanche Diodes

$V_{RSM}$	$V_{(BR)min}$ ①	$V_{RRM}$	Anode	Cathode
V	V	V	on stud	on stud
900	-	800	DS	DSI
1300	-	1200	DS	DSI
1300	1300	1200	DSA	DSAI
1700	1750	1600	DSA	DSAI
1900	1950	1800	DSA	DSAI

① Only for Avalanche Diodes

Symbol	Test	Conditions	Maximum	Ratings
$I_{F(RMS)}$	$T_{(vj)} = T_{(vj)m}$		250	A
$I_{F(AV)M}$	$T_{case} = 100^{\circ}C$ ; 180° sine		160	A
$P_{RSM}$	DSA(I) types, $T_{(vj)} = T_{(vj)m}$ , $t_p = 10 \mu s$		35	kW
$I_{FSM}$	$T_{(vj)} = 45^{\circ}C$ ; $V_R = 0$	$t = 10 \text{ ms (50 Hz), sine}$	3150	A
		$t = 8.3 \text{ ms (60 Hz), sine}$	3380	A
$I^2 t$	$T_{(vj)} = T_{(vj)m}$ ; $V_R = 0$	$t = 10 \text{ ms (50 Hz), sine}$	2800	A
		$t = 8.3 \text{ ms (60 Hz), sine}$	3000	A
$I^2 t$	$T_{(vj)} = 45^{\circ}C$ ; $V_R = 0$	$t = 10 \text{ ms (50 Hz), sine}$	49 600	A <sup>2</sup> s
		$t = 8.3 \text{ ms (60 Hz), sine}$	48 000	A <sup>2</sup> s
$T_{(vj)}$		$t = 10 \text{ ms (50 Hz), sine}$	39 200	A <sup>2</sup> s
		$t = 8.3 \text{ ms (60 Hz), sine}$	37 800	A <sup>2</sup> s
$T_{(vj)m}$			-40...+180	°C
$T_{stg}$			180	°C
$M_d$	Mounting torque		16-20	Nm
<b>Weight</b>			142-177	lb.in.
			130	g

Symbol	Test	Conditions	Characteristic	Values
$I_R$	$T_{(vj)} = T_{(vj)m}$ ; $V_R = V_{RRM}$		$\leq$	10 mA
$V_F$	$I_F = 500 \text{ A}$ ; $T_{(vj)} = 25^{\circ}C$		$\leq$	1.4 V
$V_{T0}$	For power-loss calculations only			0.85 V
$r_T$	$T_{(vj)} = T_{(vj)m}$			1.1 mΩ
$R_{thJC}$	DC current	180° sine		0.35 K/W
		180° sine		0.39 K/W
$R_{thJH}$	DC current			0.45 K/W
$d_s$	Creepage distance on surface			4.25 mm
$d_A$	Strike distance through air			4.25 mm
<b>a</b>	Max. allowable acceleration			100 m/s <sup>2</sup>

Data according to IEC 747-2

IXYS reserves the right to change limits, test conditions and dimensions

IXYS reserves the right to change limits, test conditions, and dimensions.

IXYS Corporation

3540 Bassett Street, Santa Clara, CA 95054


Tel: 408-982-0700 Fax: 408-496-0670

$V_{RRM} = 800 - 1800 \text{ V}$

$I_{F(RMS)} = 250 \text{ A}$

$I_{F(AV)M} = 160 \text{ A}$

DO-205 AC



A = Anode  
C = Cathode

### Features

- International standard package, JEDEC DO-205 AC (~DO30)
- Planar glassivated chips


### Applications

- High power rectifiers
- DC supplies
- Field supply for DC motors
- Power supplies

### Advantages

- Space and weight savings
- Simple mounting
- Improved temperature and power cycling
- Reduced protection circuits

Dimensions in mm (1 mm = 0.0394")






Fig. 1 Forward characteristics




Fig. 2 Surge overload current  
 $I_{FSM}$ : Crest value,  $t$ : duration




Fig. 3  $I^2t$  versus time (1-10 ms)




Fig. 4 Power dissipation versus forward current and ambient temperature




Fig. 5 Max. forward current at case temperature 180° sine




Fig. 6 Transient thermal impedance junction to heatsink

$R_{thJH}$  for various conduction angles  $d$ :

$d$	$R_{thJH}$ (K/W)
DC	0.45
180°	0.516
120°	0.567
60°	0.660
30°	0.733

Constants for  $Z_{thJH}$  calculation:

$i$	$R_{thi}$ (K/W)	$t_i$ (s)
1	0.06713	0.003
2	0.06242	0.094
3	0.22045	3.846
4	0.10	3.2