


**SHARP BREAKDOWN, LOW LEAKAGE
LVA REGULATOR DIODES
LVA43A - LVA100A**

- Sharper breakdown
- Lower leakage current characteristics in the 4 – 10 volt range

PART NUMBER	NOMINAL VOLTAGE	TEST CURRENT	MAX ZENER IMPEDANCE	MAX REVERSE LEAKAGE CURRENT		MAX NOISE DENSITY
	V _z @ I _{zt} (Vdc)	I _{zt} (mA)	Z _{zt} @ I _{zt} (OHMS)	I _r (µAdc)	V _r (Vdc)	@ 250 µA
LVA43A	4.3	20	18	4.0	1.5	4
LVA47A	4.7	10	15	4.0	2.0	4
LVA51A	5.1	5	15	0.1	2.0	4
LVA56A	5.6	1	40	0.05	3.0	4
LVA62A	6.2	1	50	0.05	4.0	4
LVA68A	6.8	1	50	0.05	5.0	4
LVA75A	7.5	1	100	0.01	6.0	4
LVA82A	8.2	1	100	0.01	6.5	4
LVA91A	9.1	1	100	0.01	8.0	4
LVA100A	10.0	1	100	0.01	9.0	4

Package Style		DO-7
Forward Voltage (V _f)	@ I _f = 200 mAdc	1.5 Vdc
Noise Density (Nd)	@ I _z = 250 µAdc	4.0 µV / √Hz
Power Dissipation (Pd)	@ T _a = 25° C	400 mW
Operating Temperature (T _{opr})		-65 to + 175° C
Storage Temperature (T _{stg})		-65 to + 200° C
Voltage Tolerance:	Standard Device	±10%
	Suffix A	±5%
	Suffix B	±2%

Noise Density measured from 1000 to 3000 Hz.



NJ Semi-Conductors reserves the right to change test conditions, parameter limits and package dimensions without notice. Information furnished by NJ Semi-Conductors is believed to be both accurate and reliable at the time of going to press. However, NJ Semi-Conductors assumes no responsibility for any errors or omissions discovered in its use. NJ Semi-Conductors encourages customers to verify that datasheets are current before placing orders.