


MBR7xx, MBRF7xx & MBRB7xx Series


Schottky Barrier Rectifier

Reverse Voltage 35 to 60 V
Forward Current 7.5 A


ITO-220AC (MBRF7xx)



TO-220AC (MBR7xx)



Mounting Pad Layout TO-263AB




Dimensions in inches and (millimeters)

Features

- Plastic package has Underwriters Laboratory Flammability Classifications 94V-0
- Metal silicon junction, majority carrier conduction
- Low power loss, high efficiency
- Guardring for overvoltage protection
- For use in low voltage, high frequency inverters, free wheeling, and polarity protection applications
- High temperature soldering guaranteed:
250°C/10 seconds, 0.25" (6.35mm) from case

TO-263AB (MBRB7xx)



Mechanical Data

Case: JEDEC TO-220AC, ITO-220AC & TO-263AB molded plastic body

Terminals: Plated leads, solderable per MIL-STD-750, Method 2026

Polarity: As marked

Mounting Position: Any

Mounting Torque: 10 in-lbs maximum

Weight: 0.08 ounce, 2.24 grams

MBR7xx, MBRF7xx & MBRB7xx Series

Schottky Barrier Rectifier

Maximum Ratings ($T_C = 25^\circ\text{C}$ unless otherwise noted)

Parameter	Symbol	MBR735	MBR745	MBR750	MBR760	Unit
Maximum repetitive peak reverse voltage	V_{RRM}	35	45	50	60	V
Working peak reverse voltage	V_{RWM}	35	45	50	60	V
Maximum DC blocking voltage	V_{DC}	35	45	50	60	V
Maximum average forward rectified current (SEE FIG. 1)	$I_{F(AV)}$		7.5			A
Peak repetitive forward current (sq. wave, 20 KHz) at $T_C = 105^\circ\text{C}$	I_{FRM}			15		A
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load (JEDEC Method)	I_{FSM}			150		A
Peak repetitive reverse current per leg at $t_p = 2.0\mu\text{s}$, 1KHz	I_{RRM}		1.0		0.5	A
Voltage rate of change (rated V_R)	dv/dt			10,000		V/ μs
Operating junction temperature range	T_J			-65 to +150		$^\circ\text{C}$
Storage temperature range	T_{STG}			-65 to +175		$^\circ\text{C}$
RMS Isolation voltage (MBRF type only) from terminals to heatsink with $t = 1.0$ second, $RH \leq 30\%$	V_{ISOL}			4500 (NOTE 1) 3500 (NOTE 2) 1500 (NOTE 3)		V

Electrical Characteristics ($T_C = 25^\circ\text{C}$ unless otherwise noted)

Parameter	Symbol	MBR735	MBR745	MBR750	MBR760	Unit
Maximum instantaneous forward voltage per leg (Note 4)						
at $I_F = 7.5\text{A}$, $T_C = 25^\circ\text{C}$		—		0.75		
at $I_F = 7.5\text{A}$, $T_C = 125^\circ\text{C}$	V_F	0.57		0.65		V
at $I_F = 15\text{A}$, $T_C = 25^\circ\text{C}$		0.84		—		
at $I_F = 15\text{A}$, $T_C = 125^\circ\text{C}$		0.72		—		
Maximum reverse current at DC blocking voltage	I_R	0.1		0.5		mA
		15		50		

Thermal Characteristics ($T_C = 25^\circ\text{C}$ unless otherwise noted)

Parameter	Symbol	MBR	MBRF	MBRB	Unit
Thermal resistance from junction to case and/or thermal resistance from junction to ambient	$R_{\Theta JA}$ $R_{\Theta JC}$	60 3.0	— 5.0	60 3.0	$^\circ\text{C/W}$

Notes:

- (1) Clip mounting (on case), where lead does not overlap heatsink with 0.110" offset
- (2) Clip mounting (on case), where leads do overlap heatsink
- (3) Screw mounting with 4-40 screw, where washer diameter is ≤ 4.9 mm (0.19")
- (4) Pulse test: 300 μs pulse width, 1% duty cycle

Ratings and Characteristic Curves ($T_A = 25^\circ\text{C}$ unless otherwise noted)

MBR7xx, MBRF7xx & MBRB7xx Series

FIG. 1 - FORWARD CURRENT DERATING CURVE




FIG. 2 - MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG. 3 - TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG. 4 - TYPICAL REVERSE CHARACTERISTICS




FIG. 5 - TYPICAL JUNCTION CAPACITANCE




FIG. 6 - TYPICAL TRANSIENT THERMAL IMPEDANCE

