


## HIGH VOLTAGE POWER SCHOTTKY RECTIFIER

### MAIN PRODUCT CHARACTERISTICS

<b>I<sub>F(AV)</sub></b>	<b>2 x 80 A</b>
<b>V<sub>RRM</sub></b>	<b>100 V</b>
<b>T<sub>j(max)</sub></b>	<b>150 °C</b>
<b>V<sub>F(max)</sub></b>	<b>0.68 V</b>

### FEATURES AND BENEFITS

- NEGLIGIBLE SWITCHING LOSSES
- HIGH JUNCTION TEMPERATURE CAPABILITY
- LOW LEAKAGE CURRENT
- GOOD TRADE OFF BETWEEN LEAKAGE CURRENT AND FORWARD VOLTAGE DROP
- AVALANCHE RATED
- LOW INDUCTION PACKAGE
- INSULATED PACKAGE:  
Insulating Voltage = 2500 V<sub>(RMS)</sub>  
Capacitance < 45 pF



### DESCRIPTION

High voltage dual Schottky rectifier designed for high frequency telecom and computer Switched Mode Power Supplies and other power converters.

Packaged in ISOTOP, this device is intended for use in medium voltage operation, and particularly, in high frequency circuitries where low switching losses and low noise are required.

### ABSOLUTE RATINGS (limiting values, per diode)

Symbol	Parameter			Value	Unit
V <sub>RRM</sub>	Repetitive peak reverse voltage			100	V
I <sub>F(RMS)</sub>	RMS forward current			180	A
I <sub>F(AV)</sub>	Average forward current	T <sub>c</sub> = 110°C $\delta = 0.5$	Per diode Per device	80 160	A
I <sub>FSM</sub>	Surge non repetitive forward current	tp = 10 ms sinusoidal		1000	A
I <sub>RRM</sub>	Repetitive peak reverse current	tp = 2 µs F = 1kHz square		2	A
I <sub>RSM</sub>	Non repetitive peak reverse current	tp = 100 µs square		10	A
E <sub>as</sub>	Non repetitive avalanche energy	T <sub>j</sub> = 25°C L = 30 mH I <sub>as</sub> = 8 A		90	mJ
I <sub>ar</sub>	Repetitive avalanche current	V <sub>a</sub> = 1.5 x V <sub>R</sub> typ Current decaying linearly to 0 in 1 µs Frequency limited by T <sub>j</sub> max.		8	A
T <sub>stg</sub>	Storage temperature range			-55 to +150	°C
T <sub>j</sub>	Maximum operating junction temperature			150	°C
dV/dt	Critical rate of rise of rise voltage			10000	V/µs

## STPS160H100TV

### THERMAL RESISTANCES

Symbol	Parameter	Value	Unit
R <sub>th(j-c)</sub>	Junction to case	Per leg	°C/W
		Total	°C/W
R <sub>th(c)</sub>	Coupling	0.14	°C/W

When the diodes 1 and 2 are used simultaneously:

$$\Delta T_j(\text{diode 1}) = P(\text{diode 1}) \times R_{th(j-c)}(\text{Per diode}) + P(\text{diode 2}) \times R_{th(c)}$$

### STATIC ELECTRICAL CHARACTERISTICS (per diode)

Symbol	Parameter	Tests Conditions		Min.	Typ.	Max.	Unit
I <sub>R</sub> *	Reverse leakage Current	T <sub>j</sub> = 25°C	V <sub>R</sub> = V <sub>RRM</sub>			40	µA
		T <sub>j</sub> = 125°C			13	50	mA
V <sub>F</sub> **	Forward Voltage drop	T <sub>j</sub> = 25°C	I <sub>F</sub> = 80 A			0.8	V
		T <sub>j</sub> = 125°C	I <sub>F</sub> = 80 A		0.63	0.68	
		T <sub>j</sub> = 25°C	I <sub>F</sub> = 160 A			0.92	
		T <sub>j</sub> = 125°C	I <sub>F</sub> = 160 A		0.75	0.8	
		T <sub>j</sub> = 25°C	I <sub>F</sub> = 60 A			0.75	
		T <sub>j</sub> = 125°C	I <sub>F</sub> = 60 A		0.59	0.63	
		T <sub>j</sub> = 25°C	I <sub>F</sub> = 120 A			0.87	
		T <sub>j</sub> = 125°C	I <sub>F</sub> = 120 A		0.69	0.74	


Pulse test : \* tp = 5 ms, δ < 2%

\*\* tp = 380 µs, δ < 2%


To evaluate the conduction losses use the following equation :

$$P = 0.56 \times I_{F(AV)} + 0.0015 \times I_{F}^2(\text{RMS})$$


**Fig. 1:** Average forward power dissipation versus average forward current (per diode).




**Fig. 2:** Average forward current versus ambient temperature (δ=0.5) (per diode).




**Fig. 3:** Non repetitive surge peak forward current versus overload duration (maximum values, per diode).




**Fig. 4:** Relative variation of thermal impedance junction to case versus pulse duration (per diode).




**Fig. 5:** Reverse leakage current versus reverse voltage applied (typical values, per diode).



**Fig. 6:** Junction capacitance versus reverse voltage applied (typical values, per diode) .



**Fig. 7:** Forward voltage drop versus forward current (maximum values, per diode).



## STPS160H100TV

### PACKAGE MECHANICAL DATA ISOTOP™

REF.	DIMENSIONS					
	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	11.80		12.20	0.465		0.480
A1	8.90		9.10	0.350		0.358
B	7.8		8.20	0.307		0.323
C	0.75		0.85	0.030		0.033
C2	1.95		2.05	0.077		0.081
D	37.80		38.20	1.488		1.504
D1	31.50		31.70	1.240		1.248
E	25.15		25.50	0.990		1.004
E1	23.85		24.15	0.939		0.951
E2		24.80			0.976	
G	14.90		15.10	0.587		0.594
G1	12.60		12.80	0.496		0.504
G2	3.50		4.30	0.138		0.169
F	4.10		4.30	0.161		0.169
F1	4.60		5.00	0.181		0.197
P	4.00		4.30	0.157		0.69
P1	4.00		4.40	0.157		0.173
S	30.10		30.30	1.185		1.193

- Cooling method: C
- Recommended torque value: 1.3 N.m.
- Maximum torque value: 1.5 N.m.

Ordering type	Marking	Package	Weight	Base qty	Delivery mode
STPS160H100TV	STPS160H100TV	ISOTOP	27g without screws	10	Tube

- Epoxy meets UL94,V0

Information furnished is believed to be accurate and reliable. However, STMicroelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of STMicroelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied.  
STMicroelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of STMicroelectronics.

The ST logo is a registered trademark of STMicroelectronics

© 1998 STMicroelectronics - Printed in Italy - All rights reserved.

STMicroelectronics GROUP OF COMPANIES

Australia - Brazil - Canada - China - France - Germany - Italy - Japan - Korea - Malaysia - Malta - Mexico - Morocco -  
The Netherlands - Singapore - Spain - Sweden - Switzerland - Taiwan - Thailand - United Kingdom - U.S.A.

<http://www.st.com>