

NPN SILICON RF POWER TRANSISTOR

DESCRIPTION:


The **ASI VHB25-28S** is Designed for Class C, 28 V High Band Applications up to 175 MHz.

FEATURES:

- Common Emitter
- $P_G = 8.5$ dB at 25 W/175 MHz
- **Omnigold™** Metalization System

MAXIMUM RATINGS

I_C	4.0 A
V_{CBO}	65 V
V_{CEO}	35 V
V_{EBO}	4.0 V
P_{DISS}	40 W @ $T_C = 25$ °C
T_J	-65 °C to +200 °C
T_{STG}	-65 °C to +150 °C
θ_{JC}	4.4 °C/W


CHARACTERISTICS $T_C = 25$ °C

SYMBOL	TEST CONDITIONS			MINIMUM	TYPICAL	MAXIMUM	UNITS
BV_{CEO}	$I_C = 200$ mA			35			V
BV_{CES}	$I_C = 200$ mA			65			V
BV_{EBO}	$I_E = 10$ mA			4.0			V
I_{CBO}	$V_E = 28$ V					2.0	mA
h_{FE}	$V_{CE} = 5.0$ V	$I_C = 200$ mA		5		---	---
C_{OB}	$V_{CB} = 28$ V	$f = 1.0$ MHz				50	pF
f_T	$V_{CE} = 10$ V	$I_C = 200$ mA	$f = 100$ MHz	250			MHz
P_G η_C	$V_{CC} = 28$ V	$P_{OUT} = 25$ W	$f = 175$ MHz	8.5	60		dB %